



Universal Interface
UI 770

Universal Interface UI 770

The UI 770 is the ideal universal wideband Interface box which allows the user to connect a PC, standard phone, handset, a headset of the Sennheiser contact center or office series and even a dictaphone for voice recording.

With the UI 770 you can easily switch between the headset, handset and PC, adjust the volume of the headset speaker and mute the headset microphone.

The UI 770 supports the possibility of limiting the Speaker volume by simply setting a switch. This secures compliance with the Noise of work Directive from EU (EU Directive 2003/10/EC) and will result in a reduced maximum output level for the user.

Benefits and Features:

- Dynamic Volume control™ keeps incoming calls at the same sound level and prevents sudden noises
- Sound clarity system™ reduces background noise and enhances the caller's voice
- Compatible with both wideband and narrowband headsets and phone systems
- Easy switching option between handset and handset as well as between phone and PC use
- Integrated dictaphone interface for economical and easy call recording
- Compliance with the EU Noise at work Directive with a single switch
- Automatic power save function for outstanding battery lifetime of up to 1 year
- Peace of mind - 2-year international warranty



Product Information

Product name	UI 770
Art. No.	504534
EAN No.	40 44155 080247
UPC No.	6 15104 23184 9
Product description	Universal interface box

Technical Data

Speaker signal output to headset	
Frequency response	100Hz. to 7kHz
Signal output level max.	Limited to 400mV

Microphone signal output to phone

Frequency response	100Hz. to 7kHz
Signal output level* at 94dB	0mV. to 300mV. adjustable

Packaging

Unit Weight	137 grams/4.9 ounces
Unit dimensions	32 x 91 x 101 mm/1.3 x 3.6 x 4 in
Units in distributor master carton	20 pcs
Master carton weight incl. products	10.768 kg/23.74 lbs
Dimensions master carton	430 x 335 x 330 mm/16.9 x 13.2 x 13 in
Unit pack/end user	1 pc

Delivery content

- UI 770 Interface box
- 1.5 volt C-size battery (IEC LR 14 C)
- Phone connecting cable: 4/4 modular plug (RJ9)
- Modular to easy disconnect cable (headset bottom cable)
- Instruction manual